

1		2		3		4																																																																																			
A								A																																																																																	
B								B																																																																																	
C		Specification Fields of applications: water; Maximum working pressure: PN10; Operating temperature range: -10 ~ +85℃; Valves are manufactured to BS6675; Compression connections comply with EN1254-2; Female thread connections are to ISO228; WRAS approved						C																																																																																	
D								D																																																																																	
E		<table><tr><td>11</td><td></td><td>15mm connecting nuts</td><td>BRASS</td><td>1</td><td></td></tr><tr><td>10</td><td></td><td>flat gasket</td><td>BRASS</td><td>1</td><td></td></tr><tr><td>9</td><td></td><td>15mm nozzle</td><td>BRASS</td><td>1</td><td></td></tr><tr><td>8</td><td></td><td>15mm copper sleeve</td><td>BRASS</td><td>1</td><td></td></tr><tr><td>7</td><td></td><td>Sleeve cap (15mm)</td><td>BRASS</td><td>1</td><td></td></tr><tr><td>6</td><td></td><td>circlip</td><td>SS301</td><td>1</td><td></td></tr><tr><td>5</td><td></td><td>O ring Ø5.1X1.6</td><td>NBR</td><td>2</td><td></td></tr><tr><td>4</td><td></td><td>Isolating valve plating stem</td><td>BRASS</td><td>1</td><td></td></tr><tr><td>3</td><td></td><td>O ring Ø8.6X3.2</td><td>NBR</td><td>2</td><td></td></tr><tr><td>2</td><td></td><td>Valve ball (SØ14xØ8x3)</td><td>BRASS</td><td>1</td><td></td></tr><tr><td>1</td><td></td><td>15mm service valve body</td><td>BRASS</td><td>1</td><td></td></tr><tr><td>ITEM</td><td>PART NO.</td><td>DESCRIPTION</td><td>MATERIAL</td><td>QTY.</td><td>MARK</td></tr></table>						11		15mm connecting nuts	BRASS	1		10		flat gasket	BRASS	1		9		15mm nozzle	BRASS	1		8		15mm copper sleeve	BRASS	1		7		Sleeve cap (15mm)	BRASS	1		6		circlip	SS301	1		5		O ring Ø5.1X1.6	NBR	2		4		Isolating valve plating stem	BRASS	1		3		O ring Ø8.6X3.2	NBR	2		2		Valve ball (SØ14xØ8x3)	BRASS	1		1		15mm service valve body	BRASS	1		ITEM	PART NO.	DESCRIPTION	MATERIAL	QTY.	MARK	E									
11		15mm connecting nuts	BRASS	1																																																																																					
10		flat gasket	BRASS	1																																																																																					
9		15mm nozzle	BRASS	1																																																																																					
8		15mm copper sleeve	BRASS	1																																																																																					
7		Sleeve cap (15mm)	BRASS	1																																																																																					
6		circlip	SS301	1																																																																																					
5		O ring Ø5.1X1.6	NBR	2																																																																																					
4		Isolating valve plating stem	BRASS	1																																																																																					
3		O ring Ø8.6X3.2	NBR	2																																																																																					
2		Valve ball (SØ14xØ8x3)	BRASS	1																																																																																					
1		15mm service valve body	BRASS	1																																																																																					
ITEM	PART NO.	DESCRIPTION	MATERIAL	QTY.	MARK																																																																																				
F		<table><tr><td colspan="2"></td><td colspan="2">Title</td><td colspan="2">Projection</td><td colspan="2">Scale</td><td colspan="2">Size</td></tr><tr><td colspan="2"></td><td colspan="2" rowspan="2">MF 15mmx1-2 CHR ANGLE SERVICE VALVE</td><td colspan="2" rowspan="2"></td><td colspan="2" rowspan="2">Material: ASS</td><td colspan="2" rowspan="2">Weight 85g</td></tr><tr><td colspan="2"></td></tr><tr><td colspan="2">Mrk</td><td colspan="2">Modification</td><td colspan="2">Date</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">Drawn :</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">NO. :</td><td colspan="2">Sheet</td></tr><tr><td colspan="2">Checked:</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">Appr. :</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">Tolerances unless otherwise specified: ISO 2768-mk</td><td colspan="2" rowspan="2"></td><td colspan="2">Client NO. :</td><td colspan="2">REV. 00</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr></table>								Title		Projection		Scale		Size				MF 15mmx1-2 CHR ANGLE SERVICE VALVE				Material: ASS		Weight 85g				Mrk		Modification		Date						Drawn :						NO. :		Sheet		Checked:										Appr. :												Tolerances unless otherwise specified: ISO 2768-mk				Client NO. :		REV. 00										F	
		Title		Projection		Scale		Size																																																																																	
		MF 15mmx1-2 CHR ANGLE SERVICE VALVE				Material: ASS		Weight 85g																																																																																	
Mrk		Modification		Date																																																																																					
Drawn :						NO. :		Sheet																																																																																	
Checked:																																																																																									
Appr. :																																																																																									
		Tolerances unless otherwise specified: ISO 2768-mk				Client NO. :		REV. 00																																																																																	
1		2		3		4																																																																																			